



4091A

1U RF Autosense Fault Switch and Distribution Amplifier

KEY FEATURES

- Redundant HOT SWAP Power Supplies
- 1-20 MHz Operation
- Eight Signal Outputs
- Manual Override
- Remote Control via Ethernet

The 4091A is a 1U rackmount fault sense switch that accepts two RF inputs and produces eight outputs (chosen from the two inputs). The unit comes standard with a single HOT SWAP AC power supply and can be configured with redundant HOT SWAP AC or DC power supplies. It has LED indicators that display the selected input as well as a control switch that is used to manually operate the switch or place the switch in "auto" mode. When in "auto" mode, the unit automatically switches upon failure of the selected input. In addition to front panel control, the unit can be controlled remotely via the Ethernet port on the rear of the unit.



4091A 1U RF Autosense Fault Switch and Distribution Amplifier

4091A Specifications

Unless otherwise stated, all specifications apply at 10 MHz, +13 dBm input level.

ELECTRICAL SPECIFICATIONS

- RF Input (2)
 - Frequency: 1 - 20 MHz
 - Level: 1 V RMS nominal into 50 Ω
 - Connectors: BNC female
 - Control: Locking Toggle
- RF Output (8)
 - Connectors: BNC female
 - Gain: +0.5 +/- 0.5 dB
 - Harmonics: -40 dBc typ. at +13 dBm in
 - Spurious: <-80 dBc
- SSB Phase noise
 - 1 Hz -135 dBc
 - 10 Hz -145 dBc
 - 100 Hz -155 dBc
 - 1 kHz -163 dBc
 - 10 kHz + -163 dBc
- Control & status
 - Switch between inputs
 - Set to autoswitch on input failure
 - Signal presence on all inputs and outputs
 - Green/Red LEDs on Front Panel
 - Network (RJ-45 connector)

ENVIRONMENTAL & PHYSICAL SPECIFICATIONS

- Temperature: 0°C to 40°C
- Humidity: 0 to 95% non-condensing
- Power requirements (AC Input): 90 - 264 V AC, 10W, 47 - 63 Hz
- Dimensions: 1U [-1.75" (4.44cm) x 19" (48.26cm) x 12" (30.48cm)]
- Weight: 12 lbs (5.40 Kg)

OPTIONS

- Redundant AC Power Supply
- Redundant DC Power Supply



Rear View



SYMMETRICOM, INC.
2300 Orchard Parkway
San Jose, California
95131-1017
tel: 408.433.0910
fax: 408.428.7896
info@symmetricom.com
www.symmetricom.com